

- ① FOUND 2" IP tagged RCE10467 in imbedded rock mound 3' dia. per (R3). (R1) Post in stone mound. Accepted as point for corner.
- SET (FSM) 20" in ground at point for corner, cap stamped: T6N R24E  
Deposited 2" x 24" IP along south side of monument, S27 S26  
rebuild rock mound 36" dia. by 10" high. S34 S35  
LS 3848  
1989
- ② FOUND 5/8" ReBar tagged RCE7522 in 3' dia. rock mound at old fence corner, no record, apparently set by single proportion since (R3). (R1) Post in stone mound 4' dia. by 2' high. Not accepted as point for corner.
- SET (FSM) 19" in ground at point determined by single proportion, cap stamped:  
Raised rock mound 4 1/2' dia. by 11" high from which 5/8" T6N R24E  
Rebar tagged RCE7522 bears: N.44°10'11"W., 1.60'. 1/4  
S27 S26  
LS 3848  
1989
- ③ FOUND 2" IP tagged RCE10467 in rock mound per (R3). (R1) Post in stone mound 4 1/2' dia. by 2' high. Accepted as point for corner.
- SET (FSM), at point for corner, 20" in ground, cap stamped: T6N R24E  
Deposited 2" x 24" IP on east side of monument, rebuilt rock S22 S23  
mound 3 1/2' dia. by 10" high. S27 S26  
LS 3848  
1989
- ④ FOUND (GLOM) in rock mound, cap stamped:  
Rebuilt rock mound 6' dia. by 2' high. T6N R24E  
From which BT bears: S15 S14  
S22 S23  
1925
- J. 17" DBH N.22°E., 203.8'. Healed scar.  
(R2) J. 8" N.22°15'E., 203.3'
- ⑤ FOUND (GLOM) in 4' dia. rock mound, cap stamped:  
From which BT's bear: T6N R24E  
S10 S11  
S15 S14  
1925
- LP 21" DBH S.39°W., 192.9', scribing visible.  
(R2) LP 10" S.38°30'W., 191.4'
- LP 23" DBH S.06°E., 368.9', scribing visible.  
(R2) LP 18" S.06°00'E., 361.0'
- ⑥ FOUND (GLOM) in 36" dia. by 10" high rock mound, cap stamped: 1/4  
from which BT's bears: S10  
1925
- LP 29" DBH N.28°W., 39.6', open blaze with visible axe marks.  
(R2) LP 10" N.28°W., 38.9'
- WBP 12" DBH N.23°W., 100', open scar with scribing visible.  
(R2) LP 10" N.23°30'W., 101'
- LP 15" DBH S.54°W., 53.8', healed scar  
(R2) LP 6" S.53°45'W., 54.1' (apparently slope distance) 1/4  
(GLOM) in 3' dia. by 18" high rock mound, cap stamped: S11  
S.03°37'05"E., 33.92'. (R2) S.00°58'E., 33.66' 1925
- ⑦ FOUND 2" IP tagged RCE10467 per (R3) with original corner stone along side. Corner stone 24" x 12" x 8" with "1/4" marked on side. (R1) Set stone 24" x 12" x 8".
- SET (FSM), in place of 2" IP, 20" in ground, cap stamped: T6N R24E  
Deposit 2" x 24" IP along west side of monument, deposit 1/4 S27  
original corner stone along east side of monument, raise S34  
rock mound 3' dia. by 10" high. LS 3848  
1989
- ⑧ FOUND 2" IP tagged RCE10467 per (R3). Accepted as point for corner.
- SET (FSM), in place of 2" IP, 20" in ground, cap stamped: T6N R24E  
Deposit 2" x 24" IP along east side of monument, raise rock 1/4  
mound 3' dia. x 10" high. Original BT's bear: S28 S27  
LS 3848  
1989
- JP 36" DBH S.53°W., 9.0', opened scar at base, scribed "BT",  
twin tree, north portion is BT. (R1) YP 30" S.53°W., 8.6'
- JP 21" DBH S.61°E., 36.9', scar at base. (R1) YP 12" S.58°E., 35.6'


- ⑨ FOUND original imbedded rock mound, 4 1/2' dia. with old post hole from which original BT's bear:
- JP(stump) ± 32" N.10°W., 45.0'. (R1) YP 28" N.12°W., 44.9'
- JP 27" DBH S.60°W., 46.1', scar at 3 1/2' and base. (R1) YP 24" S.60°W., 48.8'
- JP 33" DBH S.28°E., 68.2', scar at 3 1/2' and base. (R1) YP 26" S.30°E., 67.3'
- SET (FSM) 20" in ground at point of old post hole, cap stamped: T6N R24E  
Rebuild rock mound 4' dia. by 10" high from which bear: S21 S22  
S28 S27  
LS 3848  
1989
- Original BT's as described.
- RT: JP 15" DBH N.85°E., 44.4'
- 2" IP tagged RCE10467 per (R3), S.60°05'43"W., 41.66'
- ⑩ FOUND 2" IP tagged RCE10467 per (R3) in 3' dia. rock mound. Accepted as point for corner.
- SET (FSM), in place of IP, 20" in ground, cap stamped: T6N R24E  
Deposit 2" x 24" IP along south side of monument, 1/4 S22  
rebuild rock mound 3 1/2' dia. by 10" high, from which S27  
original BT's bear: LS 3848  
1989
- JP 40" DBH N.4°E., 28.5', healed scar. (R1) YP 30" North, 27.7'
- JP 37" DBH S.63°E., 20.1', healed scar. (R1) YP 28" S.61°E., 17.2'
- ⑪ FOUND original corner stone, with "1/4" chiseled on west face, in imbedded rock mound 3' N&S by 4' E&W; 2" IP tagged RCE10467 per (R3) bears East 0.40'. (R1) Set stone 27" x 15" x 8" in rock mound 4' at base by 2' high.
- SET (FSM) 21" in ground in place of corner stone, cap stamped: T6N R24E  
Deposit corner stone on west side of monument and 2" IP along 1/4  
east side of monument. Rebuilt rock mound 4' dia. by 9" high. S21 S22  
LS 3848  
1989
- ⑫ FOUND 2" IP tagged RCE10467 per (R3), no evidence of original corner stone. Accepted as point for corner.
- SET (FSM) 15" in ground in place of IP, cap stamped: T6N R24E  
Deposit 2" x 24" IP along south side of monument. S16 S15  
Rebuild rock mound 36" dia. by 15" high. S21 S22  
LS 3848  
1989
- ⑬ FOUND 2" IP tagged RCE10467 in 3' dia. rock mound per (R3). Accepted as point for corner.
- SET (FSM), in place of 2" IP, 18" in ground, cap stamped: T6N R24E  
Deposit 2" IP along west side of monument. 1/4 S15  
Rebuilt rock mound 4' dia. by 1' high. Original BT bears: S22  
LS 3848  
1989
- J 22" N.75°E., 59.3' (western trunk of clump of four junipers),  
semi healed scar. (R1) J 28" N.75°E., 58.7'
- ⑭ FOUND 2" IP tagged RCE10467 per (R4) and old faintly scribed MM post in 36" dia. imbedded rock mound. Accepted as point for corner.
- SET (FSM), in place of 2" IP, 20" in ground, cap stamped: T6N R24E  
Deposit 2" IP along north side of monument, rebuilt rock 1/4  
mound 40" dia. by 10" high. BT's bear: S16 S15  
LS 3848  
1990
- JP 34" DBH S.60°W., 36.8', healed scar.  
(R1) YP 28" S.60°W., 36.3'
- NEW BT: JP 7" DBH N.18°E., 9.00' scribed "1/4 S15 BT," tagged LS 3848
- ⑮ FOUND 2" IP tagged RCE10467 per (R4) in 4' dia. rock mound with displaced faintly scribed original corner post along side. Accepted as point for corner.
- SET (FSM), in place of IP, 20" in ground, cap stamped: T6N R24E  
Deposit IP along west side of monument. Rebuilt rock S9 S10  
mound 4' dia. by 10" high. From which bear: S16 S15  
LS 3848  
1990
- MM (dead) 8" DBH S.60°W., 5.9', old axe marks.  
(R1) MM 8" S.65°W., 7.9'
- NEW BT: J 14" DBH N.29°E., 70.3', scribed "S10 BT," tagged LS 3848

- ⑯ SEARCHED for corner. No evidence discovered. Due to "clerical error", there are no original notes for this corner. Point for corner determined by single proportion.
- SET (FSM) 15" in ground, cap stamped: T6N R24E  
Raised rock mound 5' dia. by 15" high. 1/4 S10  
Corner monument is located in young aspen grove. S15  
LS 3848  
1990
- ⑰ FOUND LP ± 30" (dead and down) with old axe marks. (R1) LP 28" N.72°W., 114.2'. Possible stump hole on fringe of aspen grove. (R1) C 10" S.55°E., 55.4'. Point for corner determined by record distances from creeks and LP BT.
- SET (FSM) 20" in ground, cap stamped: T6N R24E  
Raised rock mound 3 1/2' dia. by 10" high. 1/4  
From which bear: S9 S10  
LS 3848  
1990
- NEW BT's:  
LP 15" DBH West, 24.7', scribed "1/4 S9 BT," tagged LS 3848 (NE tree, cluster of 3)
- LP 14" DBH N.15°E., 53.8', scribed "1/4 S10 BT," tagged LS 3848
- 2" IP tagged RCE10467 per (R4) & (R5), N.34°15'45"W., 36.21'
- ⑱ FOUND (GLOM) in 4 1/2' dia. by 18" high rock mound, cap stamped: T6N R24E  
From which BT's bear: S4 S3  
S9 S10  
1925
- JP ± 36" (down remanent) N.60°W., 58', scribed face on underside.  
(R2) YP stump 34", N.60°30'W., 58.1'
- JP ± 41" stump N.77°E., ± 71', faint scribing visible. (R2) YP 30" N.77°E., 70.6'
- JP 38" stump S.44°E., ± 66'. (R2) YP 30" S.43°30'E., 65.3'
- JP 21" DBH N.50°E., 84.0', healed scar. (R2) YP 9" N.51°E., 84.5'
- JP 19" DBH S.73°E., 152.9', healed scar. (R2) YP 8" S.72°45'E., 153.1'
- JP 19" DBH S.37°W., 155.0', healed scar. (R2) YP 9" S.36°30'W., 155.8'
- JP 30" DBH N.80°W., 115.4', healed scar. (R2) YP 16" N.80°W., 115.5'

# MONUMENT DESCRIPTION LEGEND

- (R1) 1878 GOVERNMENT SURVEY  
(R2) 1925 GLO RESURVEY  
(R3) 1 PM 66  
(R4) 1 PM 80  
(R5) 1 RS 31  
(R7) 1 RS 98

- (GLOM) STANDARD 1" X 36" IP GENERAL LAND OFFICE SURVEY MONUMENT WITH 2 1/2" BRASS CAP. (2" X 36" IP AT SECTION CORNERS)
- (FSM) STANDARD 2" X 30" U.S. FOREST SERVICE ALUMINUM-MAGNETIC SURVEY MONUMENT WITH 3 1/4" ALUMINUM CAP.
- DBH DIAMETER BREST HIGH (4 1/2' ABOVE HIGH SIDE GROUND LEVEL)
- BT BEARING TREE LP LODGEPOLE PINE (TAMARACK)  
RT REFERENCE TREE MM MOUNTAIN MAHOGANY  
A ASPEN WBP WHITE BARK PINE  
C COTTONWOOD WF WHITE FIR  
J JUNIPER YP YELLOW PINE  
JP JEFFREY PINE IP IRON PIPE



## RECORD OF SURVEY No. 32-43 SECTIONS 9,10,16,20,21,22,27,& 28 TOWNSHIP 6 NORTH, RANGE 24 EAST, MDM. COUNTY OF MONO STATE OF CALIFORNIA

JAMES NICKLOS (LS 3848) & ASSOCIATES

MAY 1992